



For Enterprises

WHAT IS SESSION BORDER CONTROL

IP communications across multiple, sometimes untrusted, networks needs to be normalized, managed and secured. There is a need to guarantee interoperability of multiple devices, carriers and protocols in a transparent way to the user of the network.

Session border controllers take care of the conversion between protocols, transcoding, threat prevention, resource limiting, and accounting at the edge of VoIP networks of enterprises and carriers alike.

APPLICATIONS

SIP Trunking

Remote Worker

Hosted PBX

Skype For Business/ Lync SBC

Core Session Router and Load Balancer

BENEFITS

Network Security

Quality of Service/ Quality of Experience

TDM Resilience

Protocol Normalization

Media Services

Statistics and billing

Regulatory Compliance

Full-featured protection with easy interconnection at the edge of enterprise networks. The most cost-effective, easiest-to-provision, and easiest-to manage line of SBCs on the market.

Scalability from 25-250 sessions/calls

- Field upgradeable session expansion

All-in-one appliance for SIP and TDM connections

Traffic visualization tools

Cost-effective session-based licensing

No hidden fees

Enterprise inter-site networking and SIP trunking border control


Local security management for SMBs and small enterprises

Hardware-based transcoding

Qualified for Microsoft® Lync® and Skype for Business®









TECHNICAL SPECIFICATIONS

CAPACITIES

Max. 250 calls/sessions

Max. 120 TDM-SIP calls/sessions

Full transcoding capability

Full security (SRTP/TLS) capability

Unlimited SIP trunks

LICENSING

Only max. number of calls are licensed

Field upgradeable in 5/25/50/100 call increments

VOIP

SIP Trunking and Remote Working

SIP Intrusion Prevention

SIP Registration Scan Attack Detection

SIP Request Rate Limiting

SIP Friendly Load Limitation

SIP Registration Pass-thru

SIP Header Normalization

SIP Malformed Packet Protection

Advanced NAT Traversal Capabilities

Topology Hiding

ENUM Routing

TELEPHONY INTERFACES (OPTIONAL)

Up to 4 E1/T1s (with A101DE/A102DE/A104DE card)

Echo cancellation up to 128ms tail

Primary rate ISDN, configurable NT/TE

T1: Q.931, NI2, 4ESS, 5ESS, DMS-100

E1: Q.931, ETSI

MEDIA CAPABILITIES

Voice, Video, FAX, IM and Presence Support

Full RTP Transcoding (G.711, G.722, G.729, G.726, G.723.1, iLBC, AMR, G.722.1)

T.38 Fax Relay

NETWORKING

5x 10/100/1000 BaseT ethernet ports

IPV4, IPV6

IPV4 / IPV6 interworking

VLAN support

SESSION AND MONITORING

Multiple Session Routing Options

RTCP Statistics Reports

QoS (ToS or DSCP)

RADIUS CDR and Authentication

QoS Monitoring and Reporting

SECURITY

DDoS / DoS Attack Protection

Call Security with TLS/SRTP

Media Security with SRTP

IPSec Encryption

IP Firewall with port forwarding

Two-stage authentication

HARDWARE

Power: 60W universal internal power supply

Dimensions: 19" W x 8.15" D x 1.7" H / 431mm x 468mm x 44mm

Rack mounting clips included

1 Console port (USB to console port cable included)

2 USB ports

CALL CONTROL

Advanced XML Routing Engine

Dynamic Load Balancing and Call Routing

Multiple Call Access Control options

Least Cost Routing

Rate limiting: Call and Registration

Endpoint authentication

Media Bandwidth Policy

Intelligent media anchoring/release

DEBUGGING

Advanced troubleshooting

Web interface initiation of full media and signalling trace

Large onboard storage capacity for long term tracing

Onboard PCAP tracing, signalling and media, wireshark compatible

MANAGEMENT

Easy to use Web Interface

HTTP XML-based CDR

Real-time monitoring and debugging

TR-069 for remote provisioning

REST based interface to remotely configure SBCs

SUPPORT AND PROFESSIONAL SERVICES

Sangoma engineers are here to support your success. Whether you need technical support and software maintenance, training, consultation and installation services, Sangoma can help you. Visit sangoma.com/support or contact your Sales representative for more information.

WARRANTY

Standard 12-month warranty is included. Additional warranty services available, contact your Sales representative for more information.

In an effort to continuously improve our products Sangoma reserves the right to modify features, design or specifications at any time without prior notice or obligation.



